

MATERIAL SAFETY DATA SHEET

WOOD-TEX FACE GRADE SYN WOOD/ALL COLORS
 PRODUCT NAME: WOOD-TEX FACE GRADE SYN WOOD/ALL COLORS
 PRODUCT CODE: 3710201000
 HMIS CODES: H F R P
 2*3 0 G

SECTION 1 - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ECLECTIC PRODUCTS, INC.
 ADDRESS: 1075 ARROWSMITH
 EUGENE OR 97402

EMERGENCY PHONE : (800) 535-5053
 INFORMATION PHONE : (800) 767-4667
 DATE REVISED : 08/27/04
 DATE PRINTED : 08/27/04
 NAME OF PREPARER : Regulatory Compliance

SECTION 2 - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	mm Hg @ TEMP	VAPOR PRESSURE	PERCENT WEIGHT
-----------------------	------------	--------------	----------------	----------------

Acetone	67-64-1	185	68 DEG F	
---------	---------	-----	----------	--

OSHA PEL: TWA=500ppm; STEL=750ppm
 OSHA PEL: TWA=1000ppm; STEL=1000ppm
 Wood Dust

ACGIH TLV: TWA = 1mg/m3 (hardwood), 5mg/m3 (softwood)

ACGIH TLV: STEL = 10mg/m3 (softwood)

OSHA PEL: TWA = 15 mg/m3 (nuisance dust), 5 mg/m3 (respirable fraction)
 * Methyl Ethyl Ketone

ACGIH TLV: TWA=200 ppm (590 mg/m3); STEL=300 ppm (885 mg/m3)
 OSHA PEL: TWA=200 ppm (590 mg/m3)

Cellulose Nitrate

OSHA PEL: TWA=500 ppm (2000 mg/m3)
 Solvent Naphtha

OSHA PEL: STEL=375 ppm

ACGIH TLV: TWA=300 ppm

ACGIH TLV: STEL 375 ppm

LD50: 2920 MG/KG (dermal-rat)

LD50: 5840 MG/KG (oral-rat)

LC50: 3400 ppm (inhalation-rat)

* Zinc Stearate

OSHA PEL: TWA=15 mg/m3 total dust, 5 mg/m3 respirable fraction

Crystalline Silica
 OSHA PEL: TWA=10mg/m3 respirable dust, 30mg/m3 total dust

ACGIH TLV: TWA=0.1 mg/m3 respirable dust

Limestone and natural iron oxide used in making this product contain silica as an impurity. Prolonged exposure to respirable crystalline dust may increase the risk of developing a disabling lung disease called silicosis. The International Agency for Research on Cancer (IARC) believes there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica from occupational sources.

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. # Proposition 65 Statement: This product contains a chemical known to the State of California to cause cancer.

DOT Classification: Flammable liquid n.o.s. (contains acetone, methyl ethyl ketone), 3, UN 1993.

PgII ERG #128

Limited Quantities (0.3 gallon or less): Consumer Commodity ORM-D

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 133 DEG F
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Slower than ether.
APPEARANCE AND ODOR: Colored paste appearance with solvent odor.

SPECIFIC GRAVITY (H2O=1): 1.39
MATERIAL VOC: 0.11 lb/gal
SOLUBILITY IN WATER: NIL

VOC calculations are based on the federal EPA definition of volatile organic compound under the Clean Air Act. State and local air quality authorities may have more stringent regulation.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 1.4 DEG F
METHOD USED: Calculated
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1
UPPER: 12.8

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical

SPECIAL FIREFIGHTING PROCEDURES

Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Dangerous when exposed to heat, flame, or sparks. Easily ignited and burns rapidly with intense heat.

SECTION 5 - REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID
Avoid exposure to heat.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents, alkalis, and acids.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Carbon monoxide or carbon dioxide, nitrogen oxides and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6 - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

A single brief (minutes) exposure is not likely to cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract and may cause anesthetic or narcotic effects. (ie. headache, dizziness, drowsiness)

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN: Can cause irritation with redness, chapping, and inflammation. May cause drying or flaking of skin. EYES: Vapors may irritate eyes. Contact may cause redness, moderate to severe

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION

If work place exposure limits of product or components is exceeded (see Section II), a NIOSH/MSHA approved respirator for organic vapors is advised in the absence of proper environmental control. Sanding of cured product can create nuisance dust; wear dust respirator work station conditions should be evaluated by management to determine proper personal protective equipment.

VENTILATION

Adequate ventilation should be provided to keep vapor concentrations below acceptable exposure limits.

PROTECTIVE GLOVES

Wear resistant gloves such as natural rubber, neoprene, nitrile rubber or other impervious material.

EYE PROTECTION

Safety glasses with side shields or chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

To prevent repeated or prolonged skin contact, wear impervious clothing. Eyewash fountains and safety showers should be easily accessible.

WORK/HYGIENIC PRACTICES

Do not allow eye or skin contact. Avoid breathing vapors. Wash thoroughly after handling and before eating or drinking.

SECTION 9 - DISCLAIMER

To the best of our knowledge, the information provided herein is accurate, obtained from sources believed to be accurate. Since the conditions and methods of use of our product are beyond our control, we disclaim any and all liability arising out of the improper use of this product or the information provided herewith.